







TIMESPACE TECHNOLOGY

DVR PRODUCT SELECTOR



| | V500 | V400 | X500 | X300 | X300-16M | R500 |
|-------------------------------------|---|--|---|---|---|---|
| Features |  |  |  |  |  |  |
| Video | | | | | | |
| SD video inputs | 16 | 8 or 12 or 16 | 4 | 4 | 16 | 4 |
| IP Video inputs | 8 PoE | 1 | 4 PoE | 0 | 0 | 4 |
| IPS max per camera (PAL/NTSC) | 25/30 | 25/30 | 25/30 | 25/30 | 25/30 | 25/30 |
| IPS global (PAL/NTSC) | 200 | 100/120 or 150/180 or 200 | 100 | 200/240 | 200/240 | 100 |
| Video compression | H264 | H264 | H264 | MPEG2 | MPEG2 | H264 |
| Video resolution IP Cameras | 1080p | 1080p | 4k | n/a | n/a | 4k |
| Video resolution SD Cameras | 2CIF | 2CIF | 2CIF | D1 | D1 | 2CIF |
| Video Outputs | 4 | 2 | 2 | 1 | 2 | 1 |
| Audio | | | | | | |
| Audio inputs | 2 | 2 | 1 + 4 High Quality | 2 | 1 | 1 |
| Audio quality | 16 bit | 16 bit | 1 x 16 bit & 4 x 24 bit | 16 bit | 16 bit | 16 bit |
| Features | | | | | | |
| Alarm in | 10 | 10 | 6 | 5 | 10 | 10 |
| Alarm out | 4 | 4 | 3 | 3 | 3 | 1 |
| Motion detection | No | No | ✓ | ✓ | ✓ | No |
| Recording watermark | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| File p/word protection & encryption | coming soon | ✓ | ✓ | ✓ | ✓ | ✓ |
| Power-down timer | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Built-in camera power/connector | Yes/Neutrik 3-way | Yes/Neutrik 3-way | No | No | Yes/Molex | Yes/GX12 4-way |
| Configurable alarm switching | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| PTZ Support | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| GPS Input | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| RTSP streaming | ✓ | ✓ | ✓ | No | No | Yes |
| Built-in GSensor | ✓ | ✓ | ✓ | No (separate reqd) | ✓ | ✓ |
| Connectivity | | | | | | |
| POE | ✓ | No | ✓ | No | No | No |
| Supports CANLink | ✓ | ✓ | No | ✓ | ✓ | ✓ |
| Supports Bridge Alert | ✓ | ✓ | No | No | No | ✓ |
| Physical Characteristics | | | | | | |
| IP rating | IP50 | IP50 | IP50 | IP50 | IP50 | IP50 |
| Dimensions l x w x h (mm) | 292x132x143 | 292x132x143 | 206x136x53 | 210x120x50 | 210x120x50 | 206x136x53 |
| Voltage input | 12-40V | 11-50V | 10-30V | 12V | 12V | 10-30V |
| Conformance/Approvals | | | | | | |
| VCA Approval /E-Mark | ✓ | ✓ | No | ✓ | ✓ | ✓ |
| CE conformity | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |

All DVRs have a removable hard drive (max 2TB), removable SD card, and option of solid state disk (max 1TB)
 All DVRs are compatible with Timespace Reviewer and PCLink and LANLink software